

OWNERS MANUAL

MANUAL NO. 01

REV. DATE: 11/2022

DECWARE MODEL SE341.6



ZEN TRIODE INTEGRATED

aka Rachael

OWNERS MANUAL

DESCRIPTION

The Zen Triode Integrated is a 5~6 watt per channel - single-ended-triode amplifier using easy to find EL34/6CA7 output tubes. It has zero negative feedback for unlimited sound-stage depth and superior imaging. It features tube rectification, proprietary Decware transformers, a self-biasing circuit with a bias meter for each output tube. Like the famous SE84C 2 watt Decware amplifier, this is a purist built product with the absolute minimum number of parts and solder nodes. Between the input and output jacks there is only 1 capacitor, 2 resistors and our premium output transformers made from the finest US gain oriented silicon steel. (see section on transformers)

DUAL VOLUME VS. SINGLE VOLUME CONTROLS

When you purchase this amplifier you will have the option of setting it up with ONE volume control with 4 pair of inputs or TWO volume controls and 1 pair of inputs. Here are the pros and cons of each:

- | | |
|-------------------------|---|
| Single volume control - | Pros: Ease of Use, stereo image is always centered.
Cons: No way to adjust balance |
| Dual volume controls - | Pros: Ability to adjust balance
Cons: slightly more difficult to use. |

The main question one would have is why not simply have a volume control and a balance control? Reason: That puts two controls in the signal path instead of one. In an amplifier with only two resistors and one capacitor, adding additional parts, like these controls, in the signal path is audible. Remember, less is more and the goal is to preserve transparency - one of this amplifiers strongest traits.

Dual volume controls have another advantage besides half as many parts in the signal path when compared to a volume and balance control. With dual volume controls you can turn up one speaker by itself to a desired listening level and then turn up the other channel to match. Meaning you can make the second channel higher or lower without effecting the first channel. The advantage to doing this is that you can hear once you get close to a match between the channels, the sound stage lock-in when you hit the right spot. Since your room is non-symmetrical and your speakers are in reality not matched to within 5% of each other, having the volume exactly perfectly centered between the channels is never the perfect spot. You'll hear it when you try it. And you'll notice a small window when you get close to matched where you can actually adjust the sound stage to your room a bit better.

OWNERS MANUAL

TUBES - output

The SE34I.6 uses a single EL34/6CA7 output tube per channel. These are the larger ones on either side of the power transformer. They are run with modest voltages for increased life and better tone. NOTE: The EL34 is a true pentode and has no internal connections between the suppressor grid and cathode like the vast majority of audio tubes (6550, KT88, KT77, 6L6, 6V6 to name a few). That means other than directly heated triodes like 2A3's, 300B's for example, the EL34 is the only popular 8 pin audio tube that can be wired as a TRUE TRIODE.

Due to the unique opportunity with EL34's we developed what has come to be known as the Hazen Grid Mod, aka Christmas Comes Early Mod (CCE Mod for short), where we couple the suppressor grid to the cathode through a capacitor adding some additional clarity to the tube. This pushes this popular tube up the fidelity ladder a notch higher and as a result is the most neutral sounding tube in the amplifier.

While the CCE circuit will have no effect on the following tubes, they are still wonderful sounding alternates that can be used in your amplifier, each with its own sound and all about the same power in this particular circuit. They are: 6L6G, KT77, KT66, KT88, 6550, 7027, 6CA7 and 807 if you use the proper adapter. These are all plug in compatible alternates to the EL34 in this amplifier and require no adjustments.

OWNERS MANUAL

TUBES - input

The smaller 9 pin input tubes in this amplifier are dual triodes configured as an SRPP stage to give maximum voltage swing with the least number of parts. The only alternative is to use two gain stages with an additional coupling capacitor.

The tube used is our favorite Russian NOS military grade 6N1P-EV. (In Russian that reads 6h1n-EB, which is what is printed on the tube) Alternately you can use 6922's which are a touch less warm but slightly more dynamic and can be better focused.

Using 6DJ8's may or may not work depending on the brand and condition of the tube. This is because the voltages used are on the max end of what a 6DJ8 likes to see.

Alternately, you can also use the Russian 6N2P-EV for more gain, a more open and lively sound. There are two grades of this tube (as there is for the 6N1P) and the easy way to tell the military grade from the consumer grade is the pins. The better tubes have shiny plated pins, while the consumer grade are un-plated and dull looking. With the 6N2P the difference in sound between the two grades is pretty obvious. The better grade has more definition and is tighter. These tubes are also quiet. The consumer grade is more musical sounding, but typically noisier. The consumer grade usually requires you to have two or three pairs on hand to find one pair that is ultra quiet.

TUBES - rectifier

The rectifier tube in this amplifier is located directly in front of the power transformer. DO NOT TOUCH IT WHEN IT IS ON as it will be HOT. The amplifier typically ships with a 5U4G rectifier tube. There are many different brands of 5U4 type rectifiers both in New Old Stock (NOS) and in current production. Each will have a subtle effect on the sound of your amplifier.

There are also some compatible substitutes that you can try which include 5Y3GT and 5AR4. The 5AR4 is an indirectly heated rectifier with a soft start up so it may be a bit more expensive than the 5Y3GT and 5U4. A popular rectifier tube that many people try to substitute is the 274B. There are different manufactures and different types of 274B rectifier tubes. Of the ones we've examined, they all required no more than a 10uf capacitor in the first section of the power supply.

OWNERS MANUAL

BIASING and METERS

The SE341.6 is a self biasing, self balancing design meaning there is never a need to adjust the bias of the output tubes. The amp does it for you. It also insures that you get matched output power from each channel even if the tubes are not matched. And most importantly, when compared to the common “fixed bias” approach where you adjust the bias with a bias control, this way sounds better. The reason everyone doesn’t do it this way is because it sacrifices power. So it’s an issue of better sound or more power. We choose better sound.

If you have perfectly matched tubes, your bias meters of which there is one for each of the two output tubes, will read the same. This is typically between 40~50 millivolts per side. Of course different brands of tubes may read as much as 5 millivolts outside that window.



These bias meters will tell you at a glance if your output tubes are healthy and if they’re matched. As a completely analog device, they can tell you other things as well. For example, you can watch how long it takes the tubes to warm up and come to full bias by watching the meters when you first turn the amplifier on. If one tube takes a lot longer to arrive at its bias point than it used to it can be an early warning that there are differences developing between either your two output tubes

or the input tubes. Yes, the input tubes can effect the bias reading on the meter as well since they are coupled to the output tubes.

The bias meters also show what happens when the amp is at full power by dropping to a lower figure. For example, when the amplifier is at its maximum clean power (just before clipping) you will see the meters move in response to the music. They will dance between the bias point and 1/2 the bias point which is typically between 48 mills and 24 mills. It’s a nice visual indicator that lets you know if your amp is clipping. Decware amplifiers clip so gracefully it can be sometimes hard to notice when you have it turned up too loud. Seeing the meters plunge down below 20 mills is a certain indication that your amp is clipping at its power limit.

OWNERS MANUAL

Bias meters set up like this can also tell you at a glance if a tube has shorted or failed unexpectedly by suddenly reading abnormally high or low on one channel relative to the other channel. They can also reveal faults in a tube that may not show up until several minutes or hours after the amp has warmed up. In this case you would notice one channel consistently clips sooner than the other. This condition can not be discovered by the vast majority of tube testers, as the faulty tube will test perfectly fine, so the meters are the only way to discover this problem - which of course you would also hear - but if you ONLY heard it and did not have the meters, you would have no idea what is causing the problem.

CLIPPING

With 6N1P input tubes and a standard 2 volt source such as a CD player, the volume control can typically reach 2/3rds before the amp runs out of steam (clips). With a 6N2P the volume control will typically reach 1/2 way up before clipping.

SPEAKER BINDING POSTS - IMPEDANCE SWITCHES

The SE341.6 features heavy duty (almost bomb-proof) connectors for the speaker wires. They are the standard 5-way posts with standard spacing. They accept banana jacks, large spades, or bare wire up to 10 AWG in thickness. They are color coded with a RED and BLACK base. Black is the NEGATIVE speaker connection and RED is the positive speaker connection. There is a switch next to each pair of binding posts to set the speaker impedance between hi and lo. Please try both positions with music playing several times until you settle on the better sounding setting. Note: These switches are mirror imaged, so towards the power transformer is HI and switched pointing away from the transformer is LO.

BRIDGING INTO MONO

This amp can be run as a mono block (bridged) in two ways:

- A) Both the positive speaker jacks are connected together in parallel as are the negative jacks.
- B) The left negative jack is connected to the right positive jack (series) and the remaining two unused posts will then be used to drive the loudspeaker.

We recommend trying both ways. Way B usually sounds better and requires a small 12 inch piece of wire to connect the two binding posts.

OWNERS MANUAL

RCA OUTPUT JACKS

You can have your amplifier configured with line level outputs that can be used to drive a second amplifier or subwoofer. These RCA output jacks are located directly next to the speaker binding posts. You will find that these are healthy outputs that will make whatever is plugged into them sound more like the amplifier itself. This is possible by taking the output jacks directly from the amplifiers output transformers through a 10K resistor. That makes the signal coming out of the jacks rich with even order harmonics that can make even a solid state amp plugged into them sound more like tubes. This is of critical importance if you plan to use them in a bi-amp system where you want to drive a second amplifier or subwoofer because the second amp will have the harmonics of the first amp embedded into the signal feeding it. That ensures the signature of the SE34I.6 is carried through to the other amplifiers.

INPUT JACKS

If you have all four input jacks on your amplifier the selector switch will start with the farthest pair to the outside (near the binding posts) and finish with the nearest pair to the inside of the amp (near the power cord). Remember, the amplifier chassis has been laid out in a MIRROR IMAGE. If you configured your amp with dual volumes then you only have one pair of inputs and no selector.

POWER UP

The power switch is located in the front center of the amp. It will take approximately 20 seconds for the tubes to warm up after you turn on the switch. You can watch this happen by looking at the meters because they will be at ZERO when the amp is off, and slowly climb as the tubes are beginning to function. As a general rule is it always best to have speakers hooked up to the amp whenever it is on. If you have a volume control and IF you have it turned all the way down, it is OK to have the amplifier on without speakers connected. Having NO speakers connected and the volume control all the way up with music playing can damage the output tubes. This is true for most tube amps.


OWNERS MANUAL

DECWARE TRANSFORMERS

Since the output transformer is the only component your hearing other than the two resistors and one capacitor inside the SE34I.6 it should become obvious that this is a critical component relative to the overall fidelity of the amplifier. And given that, the quality of the power transformer and power supply in general is at the heart of the amplifiers performance.

Our transformers cores (shown left) are made with M-6 29 Gauge - 0.014" (0.355 mm) Grain Orientated Electrical Transformer Steel Lamination with steam blue oxide on the surfaces and edges to minimize stray losses between laminations.

This squared hysteresis loop iron-silicon alloy was expressly developed to provide lower core loss with higher permeability in the rolling direction. Grain oriented laminations are supplied in the stress relief annealed condition. The elementary patterns of the crystals in the material are "oriented", or arranged so that the axis of easiest magnetization is nearly parallel and aligned in the direction of rolling. The alignment is accomplished by a special cold-rolling and annealing processes. This allows the product to withstand more severe vibration and shock and enables the following:



1. Lower core losses as a consequence of design.
2. Higher initial permeability.
3. Higher permeability at higher inductions.
4. More stable VA/Temperature relationship over a wide range of ambient temperatures.
5. Most importantly, Superior Bandwidth and The Coherency Decware amplifiers are famous for.

As of April of 2015 this amplifier could be purchased with our UFO (Ultra Fidelity Output) transformers. These took an already good thing and pushed the envelope a bit harder with higher interleaves and more precision in the winding to achieve flat response out to over 80 kHz. UFO transformers are now standard in this amplifier.

OWNERS MANUAL

LOUDSPEAKERS / EARSPEAKERS


The SE34I.6 is designed to have its maximum power into 8 ohm speakers. That does not rule out all 4 or 6 ohm speakers or 12 and 16 ohm speakers. It simply means that statistically it will work best with around 8 ohms. Since the only thing that happens when you get a lot higher or lower than 8 ohms is the power output goes down, having efficient speakers may make this completely a non-issue. You can not hurt the amplifier by hooking up speakers that are more or less than 8 ohms. This includes planar magnetic ear-speakers (headphones) which are too hard to drive with conventional headphone amplifiers but may be as high as 30 or even 70 ohms. Most of the time these work just fine and sound great with this amp.

We find that some speakers rated as low as 88dB 1w/1m get loud enough on this amp to fill an average size room with a nice full sound. However, statistically 94dB or higher is ideal if you want to play music loud.

OWNERS MANUAL

POWER CORD / FUSE

Your amplifier has the highest quality fused IEC connector available. It is SUPERIOR to the Gold Plated Chinese units that are rebranded and passed off as expensive audiophile gear -at a ridiculous price. This is important because if you choose to use a high grade audiophile power cord it makes no sense to plug it into a 50 cent IEC connector, which btw is what is on a lot of amplifiers today - even some expensive ones.



The fuse is a 3 amp, 20mm glass fuse. You can use fast or slow blow type replacements in the amp. It is located INSIDE the IEC connector. To access it, remove the power cord and take a small screwdriver to pry the little door open. It will come completely out of the IEC connector and not only holds the fuse, but has a spare fuse in it as well.

OWNERS MANUAL

GROUND LOOPS, POWER STRIPS, HUM

Whenever we connect more than one audio component together we run the risk of creating a ground-loop which causes hum.

A ground loop happens when the path to ground in one component finds an easier (less resistive) path through another component via the ground or shield wire in your interconnects. This is a common problem when components are plugged into different outlets or a power strip is used, as the resistance varies at the ground point of each receptacle.

Ways to combat the problem are - try to plug everything into the same outlet when possible, do not use power strips, try to keep the length of the power cords the same.

If all else fails, you can try lifting the ground on one or more component until the hum goes away.

How to tell if you have a ground loop causing hum - simply remove all your interconnects from the input jacks of your amplifier so that the only thing hooked to it is your loudspeakers. You should hear no hum on all but the most efficient speakers and even those would sound quiet from the listening chair some 6 or 8 feet back. If you do hear hum, then it's likely the amplifier — assuming your speaker wires are not wrapped around a power cord somewhere. The most likely cause if it is the amplifier itself would be the tubes. Start by installing a new rectifier tube and see if that corrects it. If not you can systematically try the remaining tubes in the amplifier.

If the amp is acceptably quiet just hooked to your loudspeakers with no inputs connected, then hook your inputs up one component at a time and listen for hum. If you get hum, then you either have a ground loop between that component and the amplifier, or that component or the connecting cable is bad.

OWNERS MANUAL

BREAK-IN aka BURN-IN

When your amplifier is new, it will not sound as good as it does when it's several months old. The reason for this is the internal parts breaking in. The process typically involves the amp sounding a little harsh, or a little muddy, or having premature distortions when run at higher volumes. It can change from one to the other in as little as 15 minutes time. This process usually can occur during the first 100 hours of use. After the initial burn-in process, the amp will continue to season and refine over several months.

SOUND QUALITY

The fidelity of the amplifier, its frequency balance, pace, transparency, imaging and sound stage are extraordinary due to the small number of parts to get in the way of the music. That said, you will only ever hear it sound as good as the weakest link in your system, which could be cables, a preamp, your source component. The only way to hear how good the amplifier could sound would be to hook an analogue master tape machine with a live two track master tape where the recording was done with top notch microphones and engineering.

SOUND STAGE

Decware amplifiers are a benchmark for holographic sound where the music is completely 3D. In fact many people who watched movies using a two channel Decware amplifier thought there were 5 speakers playing. That said, give yourself a chance to experience it by occasionally pulling your speakers out into the room, several feet away from the walls. Tow them in to create an X just in front of your face and sit anywhere from 5 to 8 feet back. Close your eyes and we'll see ya when you return to Earth.

OWNERS MANUAL

WARRANTY

Your amplifier comes with a lifetime warranty to the original buyer. It covers defects in parts or labor. If you sell your amp for some reason, the buyer can return the amplifier to us for inspection and any updates at which point we can offer to transfer the lifetime warranty to him or her for a reasonable fee.

If your amp needs to return to the mothership, please call us first or at least e-mail with a description of the problem. Statistically 50% of all amps sent here for repair have nothing wrong with them. We can often head this off at the pass by consulting you over the phone and helping you to troubleshoot the problem. Decware amps are built to outlast you.

Returns should be sent to our main office. Please use the Return Form on our web site for the correct address and required information.

FINAL NOTE

We want this to be the best sounding amplifier you've owned and since these amps are like our children we have a vested interest in their continued success. Please call us any time you have questions or need advise on how to improve your sound, or room acoustics. We want you to love this thing as much as we do, and will bend over backwards to make sure you do.

-Steve Deckert / DECWARE